

GB

Page 1 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.05.2019 / 0001  
Replacing version dated / version: 06.05.2019 / 0001  
Valid from: 06.05.2019  
PDF print date: 07.05.2019  
PARADOR bottle of pigments H1  
PARADOR bottle of pigments H2  
PARADOR bottle of pigments D1  
PARADOR bottle of pigments D2

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**PARADOR bottle of pigments H1**  
**PARADOR bottle of pigments H2**  
**PARADOR bottle of pigments D1**  
**PARADOR bottle of pigments D2**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Paste  
Dyes/pigments

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

Manufacturer:  
Kraftec BV, De Pinckart 54, 5674 CC Nuenen, Netherlands  
Phone:+31 (0) 40 263 11 22, Fax:+31 (0) 40 291 36 09  
info@kraftec.nl

GB

Distributor:  
Parador GmbH, Millenkamp 7-8, 48653 Coesfeld, Germany  
Phone:+49 (0)2541 736-0, Fax:+49 (0)2541 736-214  
info@parador.de, www.parador.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+31 (0) 40 263 11 22 (Mo. - Fr. 08.00 - 17.00 h)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.05.2019 / 0001

Replacing version dated / version: 06.05.2019 / 0001

Valid from: 06.05.2019

PDF print date: 07.05.2019

PARADOR bottle of pigments H1

PARADOR bottle of pigments H2

PARADOR bottle of pigments D1

PARADOR bottle of pigments D2

EUH208-Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Ethanol	Substance with specific conc. limit(s) acc. to REACH-registration
Registration number (REACH)	---
Index	603-002-00-5
EINECS, ELINCS, NLP	200-578-6
CAS	64-17-5
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

Page 3 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.05.2019 / 0001  
Replacing version dated / version: 06.05.2019 / 0001  
Valid from: 06.05.2019  
PDF print date: 07.05.2019  
PARADOR bottle of pigments H1  
PARADOR bottle of pigments H2  
PARADOR bottle of pigments D1  
PARADOR bottle of pigments D2

Allergic reaction possible.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

Water jet spray/foam/CO2/dry extinguisher

##### **Unsuitable extinguishing media**

None known

#### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Toxic gases

#### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### **7.1 Precautions for safe handling**

##### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

##### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

GB

Page 4 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Store at room temperature.  
 Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Ethanol	Content %:1-5
WEL-TWA: 1000 ppm (1920 mg/m <sup>3</sup> )	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-104 SA (549 210)</li> <li>- Draeger - Alcohol 25/a Ethanol (81 01 631)</li> <li>- DFG (D) (Lösungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> </ul>	
BMGV: ---	Other information: ---	
Chemical Name	Magnesium oxide	Content %:
WEL-TWA: 10 mg/m <sup>3</sup> (total inh. dust, as Mg), (4 mg/m <sup>3</sup> ) (resp. dust and fume, as Mg)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
Chemical Name	Iron(III)oxide	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (fume, as Fe) / Rouge: 4 mg/m <sup>3</sup> (resp. dust), 10 mg/m <sup>3</sup> (total inh. dust)	WEL-STEL: 10 mg/m <sup>3</sup> (fume, as Fe)	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

Ethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,72	mg/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m <sup>3</sup>	

GB

Page 5 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3	

Iron(III)oxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Triferric tetraoxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Page 6 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.05.2019 / 0001  
Replacing version dated / version: 06.05.2019 / 0001  
Valid from: 06.05.2019  
PDF print date: 07.05.2019  
PARADOR bottle of pigments H1  
PARADOR bottle of pigments H2  
PARADOR bottle of pigments D1  
PARADOR bottle of pigments D2

Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
With danger of contact with eyes.  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Chemical resistant protective gloves (EN 374).  
If applicable  
Safety gloves made of butyl (EN 374)  
Protective Neoprene® / polychloroprene gloves (EN 374).  
Protective nitrile gloves (EN 374).  
Protective PVC gloves (EN 374)  
Minimum layer thickness in mm:  
0,5  
Permeation time (penetration time) in minutes:  
480  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.  
Protective hand cream recommended.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
Normally not necessary.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined

Page 7 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	No

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not to be expected

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

None known

### 10.5 Incompatible materials

None known

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.

Page 8 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	124,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>3000	mg/kg	Rat	OECD 451 (Carcinogenicity Studies)	24 mon
Reproductive toxicity:	NOAEL	5200	mg/kg bw/d	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	>20	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Male
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1730	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Female
Aspiration hazard:				Human being		No indications of such an effect.

GB

Page 9 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea
Experiences in humans:						Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption.

Magnesium oxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Symptoms:						drowsiness, drop in blood pressure, diarrhoea, disturbed heart rhythm, coughing, metal fume fever, muscle pains, muscle weakness, mucous membrane irritation, dizziness, nausea and vomiting.

Iron(III)oxide						
----------------	--	--	--	--	--	--

Page 10 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		Analogous conclusion
Acute toxicity, by inhalation:	LC50	>210	mg/m3	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant, Analogous conclusion, Mechanical irritation possible.
Serious eye damage/irritation:				Rabbit		Not irritant, Analogous conclusion, Mechanical irritation possible.
Symptoms:						respiratory distress, coughing, mucous membrane irritation

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

**PARADOR bottle of pigments H1**  
**PARADOR bottle of pigments H2**  
**PARADOR bottle of pigments D1**  
**PARADOR bottle of pigments D2**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

### Ethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	12340	mg/l	Daphnia magna		

Page 11 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

12.2. Persistence and degradability:			97	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,32				Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	H (Henry)		0,000138				
Toxicity to bacteria:			440	mg/l			
Other information:	COD		1,9	g/g			
Other information:	BOD5		1	g/g			

Iron(III)oxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Leuciscus idus		Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	ISO 8192	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

GB

Page 12 of 15  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.05.2019 / 0001  
 Replacing version dated / version: 06.05.2019 / 0001  
 Valid from: 06.05.2019  
 PDF print date: 07.05.2019  
 PARADOR bottle of pigments H1  
 PARADOR bottle of pigments H2  
 PARADOR bottle of pigments D1  
 PARADOR bottle of pigments D2

Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
22	Methanol		500	5000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: n.a.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.05.2019 / 0001

Replacing version dated / version: 06.05.2019 / 0001

Valid from: 06.05.2019

PDF print date: 07.05.2019

PARADOR bottle of pigments H1

PARADOR bottle of pigments H2

PARADOR bottle of pigments D1

PARADOR bottle of pigments D2

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Flam. Liq. — Flammable liquid

Eye Irrit. — Eye irritation

## Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

Page 14 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.05.2019 / 0001  
Replacing version dated / version: 06.05.2019 / 0001  
Valid from: 06.05.2019  
PDF print date: 07.05.2019  
PARADOR bottle of pigments H1  
PARADOR bottle of pigments H2  
PARADOR bottle of pigments D1  
PARADOR bottle of pigments D2

EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ERC Environmental Release Categories  
ES Exposure scenario  
etc. et cetera  
EU European Union  
EWC European Waste Catalogue  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
HGWP Halocarbon Global Warming Potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC Intermediate Bulk Container  
IBC (Code) International Bulk Chemical (Code)  
IC Inhibitory concentration  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LC lethal concentration  
LC50 lethal concentration 50 percent kill  
LCLo lowest published lethal concentration  
LD Lethal Dose of a chemical  
LD50 Lethal Dose, 50% kill  
LDLo Lethal Dose Low  
LOAEL Lowest Observed Adverse Effect Level  
LOEC Lowest Observed Effect Concentration  
LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

GB

Page 15 of 15  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.05.2019 / 0001  
Replacing version dated / version: 06.05.2019 / 0001  
Valid from: 06.05.2019  
PDF print date: 07.05.2019  
PARADOR bottle of pigments H1  
PARADOR bottle of pigments H2  
PARADOR bottle of pigments D1  
PARADOR bottle of pigments D2

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.