























Product quality		Basic 30 Vinyl with HDF core board	Basic 50 Solid vinyl	Basic 5.50 Solid vinyl					
Formats		1207 x 216 x 9.4 mm	1209 x 219 x 5 mm	598 x 294 x 5 mm					
Packaging	Pack:	7 Elements / 1.825 m ² / 17.15 Kg	8 Elements / 2.118 m ² / 20.40 Kg	10 Elements / 1.758 m ² / 16.20 Kg					
	Pallet:	36 Packs / 65.70 m ² / 632.40 Kg	42 Packs / 88.960 m ² / 871.80 Kg	48 Packs / 84.39 m ² / 792.60 Kg					
Tolerances (EN 14085)			Tolerances (DIN EN 649)						
Squareness of the elements (≤ 0.50mm)		≤ 0.30 mm		Weight per unit area	≥ 9700 g/m ²				
Determination of Linearity (≤ 0.30 mm)		≤ 0.15 mm/m							
Planeness concave / convex	along (≤ 0.50/≤ 1.0 %)	≤ 0.35/≤ 1.0 %		Squareness of the elements (≤ 0.25 mm)	≤ 0.10 mm				
	wide (≤ 0.10/≤ 0.15 %)	≤ 0.10/≤ 0.10 %							
Surface flushness	(average ≤ 0.15 mm)	average ≤ 0.10 mm		Determination of Linearity (≤ 0.35 mm/m)	≤ 0.20 mm/m				
	(max. ≤ 0.20 mm)	max. ≤ 0.15 mm							
Opening between instalat elements	(average ≤ 0.15 mm)	average ≤ 0.05 mm							
	(max. ≤ 0.20 mm)	max. ≤ 0.10 mm							
Guarantee	Domestic area	20 Years (According Parador guarantee conditions)		Notes	- Released for glue-down only by PARADOR Application Technology - cleaning an maintenance see instruction - technical changes reserved				
	Commercial area	10 Years (According Parador guarantee conditions)							
 EN 14041:08		 PARADOR, 0041 Emissionsgeprüftes Bauprodukt nach DIN-Grundsätzen ECO-INSTITUT		 TÜVRheinland ZERTIFIZIERT www.tuv.com ID 0000039917		 Qualität Fertigung überwacht Funktionalität		 ÉMISSIONS DANS L'AIR INTÉRIEUR A+	

Classification			
		Test method	Valuation
	Utility class 23 domestic areas with intensive use	EN 14085 EN 649	Living room, hall, kitchen, home office
	Utility class 31 commercial areas with low use	EN 14085 EN 649	Classrooms, small offices, shops
	Wearlayer	EN 429	0,3 mm
	Wear behavior	EN 649	T
	Surface Coating		PUR
	Reaction to fire	EN 13501-1	Vinyl with HDF core board: B _{f1} s1 Solid vinyl: C _{f1} s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,35 DS
	Staining resistance	EN 423	Grad 0, no visible changes
	Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	EN 425	Typ W, no visible changes
	Electrical behaviour	EN 1815	At the time in testing
	Thermal conductivity Underfloor heating – suitable, with the backing material and vapor barrier	EN 12664	Vinyl with HDF core board: 0,068 m ² *K/W Solid vinyl: 0,029 m ² *K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN 433	≤ 0,10 mm
	Accoustical impact noise reduction		≤ 0,05 ppm
	Dimensional stability	ISO 717-2	Vinyl with HDF core board: 15 db Solid vinyl: 13 db (auf Parador Akustic-Protect)
	Antimicrobial activity	EN 669	Vinyl with HDF core board: along and crosswise ≤0,1 % Solid vinyl: ≤ 0,25 %
	Slip resistance on an inclined plane	ISO 24336 (≤ 18 %)	≤ 16 % (only Solid vinyl:)
	REACH	ISO 22196	Antibacterial
	Disposal	DIN 51130	Surface brushed: R 9 Surface rough sawn: R 10
	Moving a furniture leg		Current requirements are complied
	Indentation-residual		Privat waste disposal with normal household waste, bulky waste possible

Changed:	QMB Parador	File:	PA_TDS_Vinyl_Basic_EN_12082014
Date:	01.06.2012	Updates at:	www.parador.de
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			12.08.2014